

19. #7000 Series - Flaw Check Liquid Dye Penetrant Inspection System

Will locate surface discontinuities or other indications on all non - porous materials (Metals, Plastics, Ceramics.....):- Cracks, Seams, Porosity, Laps, Laminations, Cold Shuts.

Used to detect welding, casting & forging defects, cracks & leaks in new - components and fatigue cracks on in - service components.

KEY FEATURES

- ★ Will detect wide spectrum of flaw sizes regard less of flaw orientation, up to 1 microns to 30 micron depth on standard Ni Cr test panel.
- ★ Superior capillary action, Non - Toxic, Non-Corrosive..... Free from halides & sulfides.....
- ★ Confirms to MIL- 1-25135, MIL STD 271, IS: 3658 - 1981 "Code of practice for liquid penetrant flaw detection ".

KEY APPLICATIONS AREA'S

Evaluation of micro surface defects & flaws in weld deposits, wrought & cast products of both Ferrous & Non-Ferrous metals, powder metallurgy parts, ceramics, plastics & glass objects.

7000 Flawchek Cleaner:

- a) Non-chlorinated solvent.
- b) Fast drying

7001 Flawchek Penetrant:

- a) Red ultra high penetration die.
- b) Specific Gravity < 1

7003 Flawchek Developer:

- a) High coverage developer
- b) Specific gravity <1

PACKING : 450ml /315gms. set of 3.12 sets/ 36 cans



20. Stanvac Stainless Steel Care Spray - Cleans & Polishes

Stanvac Stainless Steel Care Spray has been formulated to particularly serve as an antistatic cleaning and preserving care agent for mat and glossy stainless steel surfaces indoor and outdoor

KEY APPLICATIONS AREA'S

- ★ Removes and prevents finger marks
- ★ Removes grease films e.g. from range hoods and other kitchen equipments
- ★ Cleans without stripe-marks also larger surfaces
- ★ Makes treated surfaces look new and leaves a long-lasting water-repellent protective film
- ★ Prevents dirt from sticking to surfaces again



21. #8035 (RC) Rubber Care-preserves & Protects Rubber Parts

This is a multipurpose synthetic fluid that lubricates & prevents the ageing of rubber parts, Protects 'O' rings, oil seals, gaskets... from heat, moisture, lube oils....

KEY FEATURES

- ★ Preserves rubber parts - "O" rings, oil seals.
- ★ Prevents hardeing & ageing both during use & storage.
- ★ Weather - proofs & protects from-100°F to + 500°F and pressures upto 2000 PSI
- ★ Ultra pure. Contains no petroleum oils or harmful solvents.

KEY APPLICATIONS AREA'S

Especially formulated for the preservation & protection of all rubber parts- 'o' rings, oil seals, gaskets, sheeting.....

KEY SPECIFICATIONS

Bass	Acid Resistance	Weather Resistance	Protection Life
High viscosity polysiloxare rubber preservative fluid.	Excellent	Excellent	Indoor storage: 10 yrs+

PACKING : 12 x 500ml /300gms Aerosols sprays);

